



THE #1 CHOICE OF  
PAINTING PROFESSIONALS®

# ARISTOWALL®

## Interior Semi-Gloss Paint AWLL50



**DESCRIPTION:** ARISTOWALL® Semi-Gloss is an ultra-premium interior enamel formulated with advanced waterborne alkyd technology. It is ideal for interior walls, trim, moulding, cabinets, doors, kitchens, baths, and high traffic areas. ARISTOWALL Semi-Gloss exhibits application and appearance characteristics similar to traditional oil-based paint, but has less odor, dries faster, and allows for water cleanup. It develops a hard, durable finish that has excellent adhesion, hide, block resistance and reduced yellowing. (As with all oil-based finishes, it may yellow due to heat, lack of light, or when the painted surface is exposed to ammonia-based household cleaners.)

### PRODUCT INFORMATION

<b>SOLVENT TYPE:</b> Waterborne		<b>RESIN TYPE:</b> Waterborne alkyd	
<b>FINISH</b> (ASTM D 523): Semi-Gloss: 40–50% on a 60° meter after 14 days.			
<b>COLORS:</b> Colors can be store mixed or special ordered.			
<b>TINT BASES:</b> L Tintable White, M Medium, U Ultra Deep			
<b>VISCOSITY@77°F/25°C</b> (ASTM D 562): 93–103 KU			
<b>MAXIMUM VOC CONTENT</b> 50 g/L (as supplied)		<b>MAXIMUM RAVOC</b> (Reactivity-Adjusted VOC) 35 g/L	
<b>SOLIDS BY VOLUME</b> (ASTM D 2697) 42.0% ± 2%		<b>SOLIDS BY WEIGHT</b> 54.0% ± 2%	
<b>WEIGHT PER GALLON</b> (ASTM D 1475): 10.60 lbs.			

COMPOSITION BY WEIGHT	
<b>Pigment—25.8%</b>	<b>Vehicle—74.2%</b>
*Prime pigments .....23.6	Resins .....26.7
Reinforcing pigments .....2.2	Water & additives .....47.5
<i>*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.</i>	

RECOMMENDED FILM THICKNESS PER COAT	
Wet: 3.6 mils	Dry: 1.5 mils

**PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS**  
Approximately 375–425 sq. ft. per gallon, depending on surface conditions and application techniques.

**THINNING RECOMMENDATION:** This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.

<b>AVERAGE DRY TIME@77°F/25°C</b> (ASTM D 1640)	
To touch: 90 minutes	Recoat: After 4 hours

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** Quart, one-gallon, five-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.

**CLEANUP:** Warm, soapy water

**DISPOSAL:** For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit [www.dunnedwards.com](http://www.dunnedwards.com). **Do not mix with other products.**

**CONFORMS TO:** Master Painters Institute (MPI) #169; LEED 2009 IEQ Credit 4.2: Paints & Coatings; Green Seal Standard GS-11 (1st Edition); CHPS Section 01350 Emissions Testing; CRGI Green Wise™ Performance Standards

**SAFETY DATA SHEET:** Available at [www.dunnedwards.com](http://www.dunnedwards.com)

**SURFACE PREPARATION:** All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

- SPECIAL INSTRUCTIONS**
- CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on “Surface Preparation Safety” or call EPA’s National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead](http://www.epa.gov/lead) or /asbestos, or contact your state or local Health Department.
  - This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
  - Do not apply when the air or surface temperature is below 50°F.

PRIMERS		
<b>DRYWALL</b>		
Textured: Untextured: Skim-coated:	} VINYLASTIC® Premium (VNPR00)	
<b>MASONRY</b>		
Plaster: Tilt-up concrete: Poured-in-place: Brick: Concrete block:		} EFF-STOP® Premium (ESPR00)
Smooth trowel:	Medium BLOCFIL Premium (MBPR00), Smooth BLOCFIL Premium (SBPR00) or Smooth BLOCFIL Select (SBSL00) SUPER-LOC® Premium (SLPR00) or ENDURASEAL® (W 360V)	
<b>WOOD</b>		
Doors, trim:	INTER-KOTE® Premium (IKPR00), ULTRA-GRIP® Premium (UGPR00) or BLOCK-IT™ Premium (BIPR00)	
<b>SYNTHETIC WOOD</b>		
Masonite: Hardboard:	} INTER-KOTE® Premium (IKPR00), ULTRA-GRIP® Premium (UGPR00) or BLOCK-IT™ Premium (BIPR00)	
<b>METAL</b>		
Ferrous:	BLOC-RUST® Premium (BRPR00) or GALV-ALUM™ Premium (GAPR00)	
Non-ferrous:	GALV-ALUM™ Premium (GAPR00) or ULTRA-GRIP® Premium (UGPR00)	

GALV-ALUM™ is a trademark of BIEC International, Inc. used under license by Dunn-Edwards Corporation.