



THE #1 CHOICE OF
PAINTING PROFESSIONALS®

ARISTOWALL®

Interior Gloss Paint AWLL60



DESCRIPTION: ARISTOWALL® Gloss is an ultra-premium interior enamel formulated with advanced waterborne alkyd technology. It is ideal for interior walls, trim, moulding, cabinets, doors, kitchens, baths, and high traffic areas. ARISTOWALL Gloss exhibits application and appearance characteristics similar to traditional oil-based paint, but has less odor, dries faster, and allows for water cleanup. It develops a hard, durable finish that has excellent adhesion, hide, block resistance and reduced yellowing. (As with all oil-based finishes, it may yellow due to heat, lack of light, or when the painted surface is exposed to ammonia-based household cleaners.)

PRODUCT INFORMATION

SOLVENT TYPE: Waterborne		RESIN TYPE: Waterborne alkyd	
FINISH (ASTM D 523): Gloss: 70–80% on a 60° meter after 14 days.			
COLORS: Colors can be store mixed or special ordered.			
TINT BASES: L Tintable White, M Medium, U Ultra Deep			
VISCOSITY@77°F/25°C (ASTM D 562): 90–100 KU			
MAXIMUM VOC CONTENT 50 g/L (as supplied)		MAXIMUM RAVOC (Reactivity-Adjusted VOC) 35 g/L	
SOLIDS BY VOLUME (ASTM D 2697) 42.0% ± 2%		SOLIDS BY WEIGHT 54.0% ± 2%	
WEIGHT PER GALLON (ASTM D 1475): 10.50 lbs.			
COMPOSITION BY WEIGHT			
Pigment–23.8%		Vehicle–76.2%	
*Prime pigments23.8		Resins29.0	
		Water & additives47.2	
<i>*Prime pigments include titanium dioxide (TiO₂), plus all other pigments directly adding to the hiding power of this paint.</i>			
RECOMMENDED FILM THICKNESS PER COAT			
Wet: 3.6 mils		Dry: 1.5 mils	
PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS			
Approximately 375–425 sq. ft. per gallon, depending on surface conditions and application techniques.			
THINNING RECOMMENDATION: This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.			
AVERAGE DRY TIME@77°F/25°C (ASTM D 1640)			
To touch: 90 minutes		Recoat: After 4 hours	
APPLICATION EQUIPMENT: Brush, roller, airless spray			
PACKAGING: Quart, one-gallon, five-gallon containers			
STORAGE: Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.			
CLEANUP: Warm, soapy water			
DISPOSAL: For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit www.dunnedwards.com . Do not mix with other products.			
CONFORMS TO: Master Painters Institute (MPI) #157; LEED 2009 IEQ Credit 4.2: Paints & Coatings; Green Seal Standard GS-11 (1st Edition); CHPS Section 01350 Emissions Testing; CRGI Green Wise™ Performance Standards			
SAFETY DATA SHEET: Available at www.dunnedwards.com			
SURFACE PREPARATION: All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.			

SPECIAL INSTRUCTIONS

- CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on “Surface Preparation Safety” or call EPA’s National Lead Information Hotline at 1-800-424-LEAD, or visit www.epa.gov/lead or /asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Do not apply when the air or surface temperature is below 50°F.

PRIMERS

DRYWALL

Textured:
Untextured:
Skim-coated:

} VINYLASTIC® Premium (VNPR00)

MASONRY

Plaster:
Tilt-up concrete:
Poured-in-place:
Brick:
Concrete block:

} EFF-STOP® Premium (ESPR00)

Medium BLOCFIL Premium (MBPR00),
Smooth BLOCFIL Premium (SBPR00) or
Smooth BLOCFIL Select (SBSL00)
SUPER-LOC® Premium (SLPR00) or
ENDURASEAL® (W 360V)

WOOD

Doors, trim:

INTER-KOTE® Premium (IKPR00),
ULTRA-GRIP® Premium (UGPR00) or
BLOCK-IT™ Premium (BIPR00)

SYNTHETIC WOOD

Masonite:
Hardboard:

} INTER-KOTE® Premium (IKPR00),
ULTRA-GRIP® Premium (UGPR00) or
BLOCK-IT™ Premium (BIPR00)

METAL

Ferrous:

BLOC-RUST® Premium (BRPR00) or
GALV-ALUM™ Premium (GAPR00)

Non-ferrous:

GALV-ALUM™ Premium (GAPR00) or
ULTRA-GRIP® Premium (UGPR00)

GALV-ALUM™ is a trademark of BIEC International, Inc. used under license by Dunn-Edwards Corporation.