



THE #1 CHOICE OF  
PAINTING PROFESSIONALS®

# BLOCK-IT® Aerosol

## Interior/Exterior Stain-Blocking Primer

### BIPR00-0-WH-13

**DESCRIPTION:** **BLOCK-IT® Aerosol** is a high-hiding, all purpose, primer-sealer and stain blocker. It blocks and seals stains caused by water, nicotine, smoke, tannin, pencil, ink, grease, and felt marker, and seals smoke and pet odors. **BLOCK-IT Aerosol** can be used on interior or exterior wood, drywall, or non-galvanized metal, including hard-to-stick surfaces such as railings, shutters and outdoor furniture.

## PRODUCT INFORMATION

**SOLVENT TYPE:** Acetone, Aliphatic Hydrocarbons

**RESIN TYPE:** Styrene Acrylate Copolymer

**FINISH** Flat

**COLORS:** White. may be tinted with up to 2 fl. oz. of Dunn-Edwards ZTC Zero VOC colorant per gallon.

<b>MAXIMUM VOC CONTENT</b> <60% by weight	<b>PRODUCT-WEIGHTED MIR</b> <1.2g O3/g of product
--	--

**RECOMMENDED DRY FILM THICKNESS**

Dry: 1.5–2.5 mils (37.5–62.5 )

**PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS**

Approximately 10–12 sq. ft./can

**AVERAGE DRY TIME@77°F/25°C** (ASTM D 1640)

To touch: 30 minutes                      Recoat: 1 hour

Dry times and recoat times are temperature, humidity and film thickness dependent.

**PACKAGING:** 13 oz aerosol can

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See *Paint Storage Best Practices* Technical Bulletin at [dunnedwards.com](http://dunnedwards.com) for more information.

**CLEANUP:** Clean up wet paint with acetone. Properly discard empty container. Do not burn or place container in home trash compactor.

**DISPOSAL:** For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit [www.dunnedwards.com](http://www.dunnedwards.com). **Do not mix with other products.**

**SAFETY DATA SHEET:** Available at [www.dunnedwards.com](http://www.dunnedwards.com)

**SURFACE PREPARATION:** All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

**SPECIAL INSTRUCTIONS**

- **CAUTION:** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on “Surface Preparation Safety” or call EPA’s National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead](http://www.epa.gov/lead) or/asbestos, or contact your state or local Health Department.
- Shake aerosol can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle, **DO NOT STRIKE CAN**, contact Dunn-Edwards. Shake often during use. Hold can upright 10–16” from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can at the same distance from the surface and in constant motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs.
- **DO NOT USE NEAR OPEN FLAME.**
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Do not apply when the air or surface temperature is below 50° F or greater than 90° F. The relative humidity should not be greater than 85%.

**PRIMERS**

**DRYWALL**

Textured:	}	<b>BLOCK-IT® Aerosol (BIPR00)</b>
Untextured:		
Skim-coated:		

**MASONRY**

Plaster:	}	<b>BLOCK-IT® Aerosol (BIPR00)</b>
Tilt-up concrete:		
Poured-in-place:		
Brick:		
Concrete block:		<b>BLOCK-IT® Aerosol (BIPR00)</b>
Smooth trowel:		<b>BLOCK-IT® Aerosol (BIPR00)</b>

**WOOD**

Trim, sash, fascia:	}	<b>BLOCK-IT® Aerosol (BIPR00)</b>
T1-11 siding:		

**SYNTHETIC WOOD**

Masonite:	}	<b>BLOCK-IT® Aerosol (BIPR00)</b>
Hardboard:		
HDO siding:		

**METAL**

Ferrous:	<b>BLOCK-IT® Aerosol (BIPR00)</b>
----------	-----------------------------------