



CEILING PAINT

Low Odor | Zero VOC

Interior Flat Classic White

CLPT10



DESCRIPTION: Dunn's™ Ceiling Paint is a Zero VOC, premium, spatter resistant, latex flat ceiling paint for use on interior smooth, textured, popcorn and acoustic ceilings. It helps to hide minor surface imperfections and provides excellent hide and coverage. It is ideal for use on properly prepared interior ceilings including drywall, plaster, concrete, masonry and wood.

PRODUCT INFORMATION

SOLVENT TYPE: Waterborne | **RESIN TYPE:** Copolymer

FINISH (ASTM D 523): Flat: 0.2–2% on a 60° meter; 1–2% on an 85° meter

COLORS: Stock colors: Classic White only.

VISCOSITY@77°F/25°C (ASTM D 562): 100–110 KU

MAXIMUM VOC CONTENT | **MAXIMUM RAVOC** (Reactivity-Adjusted VOC)

2 g/L (by ASTM Test Method D 6886) | 1 g/L
 NOTE: "Zero VOC" means "No organic solvents added." (Trace amounts of VOC may be present as residual components of other ingredients. Dunn-Edwards uses Zero VOC colorants; other additives may increase VOC emissions.)

SOLIDS BY VOLUME (ASTM D 2697) | **SOLIDS BY WEIGHT**
 38% ± 2% | 57% ± 2%

WEIGHT PER GALLON (ASTM D 1475): 11.71 lbs.

COMPOSITION BY WEIGHT

Pigment—43%	Vehicle—57%
*Prime pigments 16.0	Resin Solids..... 10.0
Reinforcing pigments..... 27.0	Water & additives 47.0

*Prime pigments include all pigments directly adding to the hiding power of this paint.

RECOMMENDED FILM THICKNESS PER COAT

Wet: 3.8 mils | Dry: 1.5 mils

PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS

Approximately 350–400 sq. ft. per gallon, depending on surface conditions and application techniques.

THINNING RECOMMENDATION: This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. However, if thinning is necessary to maintain good flow and workability, add up to 1/4 pint (4 fl. oz.) of water per gallon of coating.

AVERAGE DRY TIME@77°F/25°C

To touch: 30–60 minutes | Recoat: 1–2 hours
 Dry times and recoat times are temperature, humidity and film thickness dependent.

APPLICATION EQUIPMENT: Brush, roller, airless spray

PACKAGING: One-gallon

STORAGE: Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See *Paint Storage Best Practices* Technical Bulletin at dunnedwards.com for more information.

CLEANUP: Warm, soapy water

DISPOSAL: For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit www.dunnedwards.com. **Do not mix with other products.**

CONFORMS TO: ARB 2007 SCM & CALGreen 2019; LEED 2009 IEQ Credit 4.2

SAFETY DATA SHEET: Available at www.dunnedwards.com

SURFACE PREPARATION: All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

HEALTH & SAFETY: CAUTION! INHALATION OF SPRAY MIST OR SANDING DUST MAY BE HARMFUL. Use only with adequate ventilation. Avoid breathing vapors, spray mist and sanding dust. Wear NIOSH-approved N95 particulate filter mask when spraying or sanding. Avoid contact with skin and eyes. Do not ingest. Close container after each use. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water to drink – for emergency information, call 1-800-222-1222. If having difficulty breathing, move to fresh air. For eye contact, immediately flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water.

• KEEP OUT OF REACH OF CHILDREN •

Ingredient (CAS #): Water (7732-18-5); Titanium Dioxide (13463-67-7); Nepheline Syenite (37244-96-5); Copolymer Resin (Proprietary); Kaolin, Calcined (92704-41-1).

SPECIAL INSTRUCTIONS

- CAUTION! Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Wear a NIOSH-approved N95 particulate filter mask to avoid breathing dust. Use a HEPA vacuum for cleanup, and finish by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call U.S. EPA's lead hotline at 1-800-424-LEAD, or visit www.epa.gov/lead or / asbestos, or contact your state or local Health Agency.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Mildew-Resistant - This paint contains a preservative which inhibits the growth of mildew on the surface of this paint film.
- On Level 4 and 5 Drywall Finishes, use **VINYLASTIC Plus** thinned with 10% of clean water (3/4 pints per gallon or 1/2 gallon per 5-gallons) for best penetration.
- Do not apply when the air or surface temperature is below 50°F.

PRIMERS

DRYWALL

Textured: **2 Coats Dunn's Ceiling Paint (CLPT10)**
 Untextured: **2 Coats Dunn's Ceiling Paint (CLPT10)**
 Skim-coated: **VINYLASTIC® Plus (VNPL00)**

MASONRY

**Cured with pH of less than 9

Plaster: }
 Tilt-up concrete: } **2 Coats Dunn's Ceiling Paint (CLPT10)****,
 Poured-in-place: } **EFF-STOP® Select (ESSL00)** or
 Brick: } **FLEX-PRIME® Select (FPSL00)**
 Smooth trowel: **SUPER-LOC® Premium (SLPR00)**
 Concrete block: **Smooth BLOCFIL Premium (SBPR00)** or
Smooth BLOCFIL Select (SBSL00)

WOOD/SYNTHETIC WOOD-INTERIOR

Trim, doors: } **DECOPRIME™ (DCPR00)**,
 Masonite: } **ULTRA-GRIP® Premium (UGPR00)** or
 Hardboard: } **ULTRA-GRIP® Select (UGSL00)**

METAL

Ferrous: **BLOC-RUST® Premium (BRPR00)** or
ENDURAPRIME® Metal Primer (ENPR00)
 Non-ferrous: **ULTRASHIELD® Galvanized Metal Primer (ULGM00)** or
BLOC-RUST® Premium (BRPR00)
 Galvanized steel: **ULTRASHIELD® Galvanized Metal Primer (ULGM00)** or
***ULTRA-GRIP® Premium (UGPR00)**

*for incidental use on galvanized