



THE #1 CHOICE OF  
PAINTING PROFESSIONALS®

# PREP-WALL™

## Interior Drywall Surface Conditioner PRWL00



**DESCRIPTION:** PREP-WALL™ is a professional interior surface conditioner that improves the quality of the drywall finish. It provides a smooth, sandable surface, eliminating problems often caused by porosity variations between finished joints and untreated drywall. PREP-WALL is recommended for new drywall to minimize texture variations from drywall face paper and joint cements. **It is not, and should not be considered as a sealer, primer or a finished top coat.**

### PRODUCT INFORMATION

<b>SOLVENT TYPE:</b> Water		<b>RESIN TYPE:</b> Vinyl Acetate Latex	
<b>FINISH</b> (ASTM D 523): Flat: 1–2% on a 60° meter			
<b>COLORS:</b> White. PREP-WALL may be tinted with up to 2 fl. oz. of Dunn-Edwards ZTC Zero VOC colorant per gallon.			
<b>VISCOSITY@77°F/25°C</b> (ASTM D 562): 95–101 KU			
<b>MAXIMUM VOC CONTENT</b> 25 g/L (as supplied)		<b>MAXIMUM RAVOC</b> (Reactivity-Adjusted VOC) 10 g/L	
<b>SOLIDS BY VOLUME</b> (ASTM D 2697) 45% ± 2%		<b>SOLIDS BY WEIGHT</b> 47% ± 2%	
<b>WEIGHT PER GALLON</b> (ASTM D 1475): 11.7 lbs.			
<b>RECOMMENDED FILM THICKNESS PER COAT</b> Wet: 8-10 mils			
<b>PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS</b> Approximately 200 sq. ft. per gallon, depending on surface conditions and application techniques.			
<b>THINNING RECOMMENDATION:</b> This coating may be thinned by adding no more than 16 oz. per gallon of clean water. Do not overthin. Mix by stirring. Power mixing at high RPM is not recommended.			
<b>AVERAGE DRY TIME@77°F/25°C</b> (ASTM D 1640) To touch: 45–60 minutes      Recoat: 12 hours Dry times and recoat times are temperature, humidity and film thickness dependent.			
<b>APPLICATION EQUIPMENT:</b> Roller application: 3/8" to 1/2" nap roller; Airless sprayer: Minimum pump capacity of one gallon per minute. Recommended tip size .019" - .021"			
<b>PACKAGING:</b> Five-gallon containers			
<b>STORAGE:</b> Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See <i>Paint Storage Best Practices</i> Technical Bulletin at <a href="http://dunnedwards.com">dunnedwards.com</a> for more information.			
<b>CLEANUP:</b> Warm, soapy water			
<b>DISPOSAL:</b> For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit <a href="http://www.dunnedwards.com">www.dunnedwards.com</a> . <b>Do not mix with other products.</b>			
<b>CONFORMS TO:</b> ARB 2007 SCM & CALGreen 2013; LEED 2009 IEQ Credit 4.2			
<b>SAFETY DATA SHEET:</b> Available at <a href="http://www.dunnedwards.com">www.dunnedwards.com</a>			

#### SPECIAL INSTRUCTIONS

- **CAUTION:** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or log onto [www.epa.gov/lead](http://www.epa.gov/lead) or/asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Do not apply when the air or surface temperature is below 50°F.

#### USE AS A SURFACE CONDITIONER FOR

DRYWALL



PREP-WALL™ (PRWL00)