



THE #1 CHOICE OF  
PAINTING PROFESSIONALS®

# RECOVER®

## Interior/Exterior Recycled Latex Paint



**DESCRIPTION:** RECOVER® is an interior/exterior latex paint for use on properly prepared drywall, masonry, wood, and metal. This recycled product is made with a minimum of 50% post-consumer paint and offers an affordable alternative for state and local government projects and graffiti abatement programs.

### PRODUCT INFORMATION

**SOLVENT TYPE:** Waterborne

**RESIN TYPE:** Mixed Latex

**FINISHES**

**RE-F Series** (Flat): 10% max on an 85° meter

**RE-E Series** (Eggshell): 15-25% on an 60° meter

**RE-S Series** (Semi-Gloss) 30-50% on an 60° meter

**COLORS:** Whipped White, Ivory White, Tawny Beige, Grizzler Gray, Concrete Gray, and Chocolate Brown. Other colors can be special ordered.

**VISCOSITY@77°F/25°C** (ASTM D 562): 80-100 KU

**MAXIMUM VOC CONTENT**

150 g/L (as supplied)

**SOLIDS BY VOLUME** (ASTM D 2697)

30-40%

**SOLIDS BY WEIGHT**

40-55%

**WEIGHT PER GALLON** (ASTM D 1475)

10.0 lbs.

**COMPOSITION BY WEIGHT**

*\*This product consists primarily of post-consumer recyclable latex paints. Composition of finished product may vary with feedstocks.*

**RECOMMENDED FILM THICKNESS PER COAT**

Wet: 4.3-5.0 mils

Dry: 1.5 mils

**PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS**

Approximately 250-350 sq. ft. per gallon, depending on surface conditions and application techniques.

**THINNING RECOMMENDATION:** This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.

**AVERAGE DRY TIME@77°F/25°C** (ASTM D 1640)

To touch: 30-60 minutes

Recoat: 2-4 hours

Dry times and recoat times are temperature, humidity and film thickness dependent.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** One-gallon, Five-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See *Paint Storage Best Practices* Technical Bulletin at [dunnedwards.com](http://dunnedwards.com) for more information.

**CLEANUP:** Warm, soapy water

**DISPOSAL:** For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit [www.dunnedwards.com](http://www.dunnedwards.com). **Do not mix with other products.**

**CONFORMS TO:** ARB 2007 SCM & CALGreen 2013; LEED 2009 IEQ Credit 4.2

**SAFETY DATA SHEET:** Available at [www.dunnedwards.com](http://www.dunnedwards.com)

**SURFACE PREPARATION:** All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

**SURFACE PREPARATION**

Wash surface with water, using a hose with a pressure nozzle or a lower-powered high-pressure washer. Remove clinging dirt with a broom or brush. Remove loose paint and deteriorated foam and patch where necessary. Allow surface to thoroughly dry before application.

**SPECIAL INSTRUCTIONS**

- **CAUTION:** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead](http://www.epa.gov/lead) or/asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- **RECOVER** meets federal performance specifications for recycled latex paint. For projects with more demanding performance requirements, consult your Dunn-Edwards Sales Representative.
- New surfaces must be primed with a suitable Dunn-Edwards primer. On previously painted surfaces, spot-prime bare or patched areas or prime entire surface as required.
- Do not apply during rainy weather, high humidity, or when the air or surfaces temperature is below 50°F.