



THE #1 CHOICE OF
PAINTING PROFESSIONALS®

SURFACO® Select

Interior/Exterior Chalk-Binding Primer

SFSL00-1



DESCRIPTION: SURFACO® Select is an ultra-low VOC, low odor, interior and exterior penetrating chalk-binding primer. It is ideal for use on previously painted, chalky surfaces. Its formulation provides maximum penetration and adhesion that binds and holds residual chalky materials to the surface. It has good alkali and efflorescence resistance.

PRODUCT INFORMATION

SOLVENT TYPE: Waterborne **RESIN TYPE:** Acrylic

FINISH (ASTM D 523): 50–60% on a 60° meter

COLORS: Clear. may be tinted with up to 2 fl. oz. of Dunn-Edwards ZTC Zero VOC colorant per gallon.

VISCOSITY@77°F/25°C (ASTM D 562): 44 KU

MAXIMUM VOC CONTENT 10 g/L (as supplied)	MAXIMUM RAVOC (Reactivity-Adjusted VOC) 3 g/L
--	---

SOLIDS BY VOLUME (ASTM D 2697) 9.28%	SOLIDS BY WEIGHT 10%
--	--------------------------------

RECOMMENDED FILM THICKNESS PER COAT

Dry: 1.5 mils

PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS

Approximately 200–300 sq. ft. per gallon, depending on surface conditions and application techniques.

THINNING RECOMMENDATION: This coating is intended to be applied without thinning or diluting under normal environmental and application conditions.

AVERAGE DRY TIME@77°F/25°C (ASTM D 1640)

To touch: 15 minutes Recoat: 2–4 hours
Dry times and recoat times are temperature, humidity and film thickness dependent.

APPLICATION EQUIPMENT: Brush, roller, airless spray, garden sprayer

PACKAGING: One-gallon, five-gallon containers

STORAGE: Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See *Paint Storage Best Practices* Technical Bulletin at dunnedwards.com for more information.

CLEANUP: Warm, soapy water

DISPOSAL: For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit www.dunnedwards.com. **Do not mix with other products.**

CONFORMS TO: ARB 2007 SCM & CALGreen 2013; LEED 2009 IEQ Credit 4.2

SAFETY DATA SHEET: Available at www.dunnedwards.com

SURFACE PREPARATION: All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

SPECIAL INSTRUCTIONS

- CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on “Surface Preparation Safety” or call EPA’s National Lead Information Hotline at 1-800-424-LEAD, or visit www.epa.gov/lead or /asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Do not apply when the air or surface temperature is below 50°F.

INTENDED USES

PREVIOUSLY PAINTED } SURFACO® Select (SFSL00) or
CHALKY SURFACES } SUPER-LOC® Premium (SLPR00)