



THE #1 CHOICE OF PAINTING PROFESSIONALS®

# SURFACO® Select

## Interior/Exterior Chalk-Binding Primer

### SFSL00



**DESCRIPTION:** SURFACO® Select is an ultra-low VOC, low odor, interior and exterior penetrating chalk-binding primer. It is ideal for use on previously painted, chalky surfaces. Its formulation provides maximum penetration and adhesion that binds and holds residual chalky materials to the surface. It has good alkali and efflorescence resistance.

### PRODUCT INFORMATION

**SOLVENT TYPE:** Waterborne      **RESIN TYPE:** Acrylic

**FINISH** (ASTM D 523): 50–60% on a 60° meter

**COLORS:** Clear. may be tinted with up to 2 fl. oz. of Dunn-Edwards ZTC Zero VOC colorant per gallon.

**VISCOSITY@77°F/25°C** (ASTM D 562): 44 KU

**MAXIMUM VOC CONTENT**      **MAXIMUM RAVOC** (Reactivity-Adjusted VOC)  
10 g/L (as supplied)      3 g/L

**SOLIDS BY VOLUME** (ASTM D 2697)      **SOLIDS BY WEIGHT**  
9.28%      10%

**PRACTICAL COVERAGE PER COAT - Approx. sq. ft per gallon**

Stucco/Simulated Brick .....	<b>150</b>
Concrete Slab/Tilt-ups .....	<b>175</b>
Concrete Blocks.....	<b>80</b>
Brick .....	<b>125</b>
Adobe .....	<b>100</b>
Chalky Surfaces.....	<b>300</b>

**Note:** Actual coverage will vary depending on porosity of surface. Use a high solids formula, like Smooth BLOCFIL Premium/Select for low density, decorative block (*split-face/fluted block*).

**THINNING RECOMMENDATION:** This coating is intended to be applied without thinning or diluting under normal environmental and application conditions.

**AVERAGE DRY TIME@77°F/25°C** (ASTM D 1640)  
To touch: 15 minutes      Recoat: 2–4 hours  
Dry times and recoat times are temperature, humidity and film thickness dependent.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray, garden sprayer

**PACKAGING:** One-gallon, five-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See *Paint Storage Best Practices* Technical Bulletin at [dunnedwards.com](http://dunnedwards.com) for more information.

**CLEANUP:** Warm, soapy water

**DISPOSAL:** For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit [www.dunnedwards.com](http://www.dunnedwards.com). **Do not mix with other products.**

**CONFORMS TO:** ARB 2007 SCM & CALGreen 2013; LEED 2009 IEQ Credit 4.2

**SAFETY DATA SHEET:** Available at [www.dunnedwards.com](http://www.dunnedwards.com)

**SURFACE PREPARATION:** All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

### SPECIAL INSTRUCTIONS

- **CAUTION:** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead](http://www.epa.gov/lead) or /asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Do not apply when the air or surface temperature is below 50°F.

### INTENDED USES

PREVIOUSLY PAINTED CHALKY SURFACES



SURFACO® Select (SFSL00) or SUPER-LOC® Premium (SLPR00)