



THE #1 CHOICE OF  
PAINTING PROFESSIONALS®

# SPARTAWALL®

## Low Odor | Zero VOC

### Interior Eggshell Paint

#### SWLL30



≤ 5 g/L VOC\*\*

**DESCRIPTION:** SPARTAWALL® Eggshell is a premium interior, Zero VOC, acrylic eggshell paint that has very low odor and no added organic solvents. SPARTAWALL Eggshell is ideal for use on residential and commercial projects, schools, hospitals, and in other occupied spaces where low odor products are preferred. SPARTAWALL Eggshell forms a tough, washable finish ideal for use in high traffic areas, walls, trim and doors, window frames, and handrails.

## PRODUCT INFORMATION

**SOLVENT TYPE:** Waterborne **RESIN TYPE:** Modified copolymer

**FINISH** (ASTM D 523): Eggshell: 10–15% on a 60° meter; 15–30% on an 85° meter

**COLORS:** Colors can be special ordered or store mixed.

**TINT BASES:** L Tintable White, M Medium, U Ultra Deep

**VISCOSITY@77°F/25°C** (ASTM D 562): 100–105 KU

**MAXIMUM VOC CONTENT** 2 g/L (by ASTM Test Method D 6886) **MAXIMUM RAVOC** (Reactivity-Adjusted VOC) 1 g/L  
NOTE: "Zero VOC" means "No organic solvents added." (Trace amounts of VOC may be present as residual components of other ingredients. Dunn-Edwards uses Zero VOC colorants; other additives may increase VOC emissions.)

**SOLIDS BY VOLUME** (ASTM D 2697) 36.0% ± 2% **SOLIDS BY WEIGHT** 47.0% ± 2%

**WEIGHT PER GALLON** (ASTM D 1475): 10.39 lbs.

### COMPOSITION BY WEIGHT

**Pigment–26.7%** **Vehicle–73.3%**  
\*Prime pigments ..... 16.6 Acrylic resins ..... 17.9  
Reinforcing pigments ..... 10.1 Water & additives ..... 55.4  
\*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.

### RECOMMENDED FILM THICKNESS PER COAT

Wet: 4.2 mils Dry: 1.5 mils

### PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS

Approximately 325–375 sq. ft. per gallon, depending on surface conditions and application techniques.

**THINNING RECOMMENDATION:** This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.

### AVERAGE DRY TIME@77°F/25°C

To touch: 30–60 minutes Recoat: 1–2 hours  
Dry times and recoat times are temperature, humidity and film thickness dependent.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** One-gallon, five-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See *Paint Storage Best Practices* Technical Bulletin at [dunnedwards.com](http://dunnedwards.com) for more information.

**CLEANUP:** Warm, soapy water

**DISPOSAL:** For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit [www.dunnedwards.com](http://www.dunnedwards.com). **Do not mix with other products.**

**CONFORMS TO:** ARB 2007 SCM & CALGreen 2016; CA Section 01350; LEED 2009 IEQ Credit 4.2; LEED v4 EQ Credit 2; MPI Approved Product #52; CRGI Green Wise Certified Gold; FDA Guidelines for Resinous & Polymeric Coatings

**SAFETY DATA SHEET:** Available at [www.dunnedwards.com](http://www.dunnedwards.com)

**SURFACE PREPARATION:** All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

### SPECIAL INSTRUCTIONS

- CAUTION!** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Wear a NIOSH-approved N95 particulate filter mask to avoid breathing dust. Use a HEPA vacuum for cleanup, and finish by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call U.S. EPA's lead hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead](http://www.epa.gov/lead) or / asbestos, or contact your state or local Health Agency.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- This paint contains a preservative which inhibits the growth of mold and mildew on surface of this paint film.
- \*On Level 4 and 5 Drywall Finishes, thin drywall primer with 10% water (3/4 pints per gallon; 1/2 gallon per 5-gallons) for best penetration.
- Do not apply when the air or surface temperature is below 50°F.

### PRIMERS

#### DRYWALL

Textured: } **Self-priming** (first coat)  
Untextured: }

Skim-coated: } **\*VINYLASTIC® Plus (VNPL00)**  
Level 4 and 5 drywall finishes } (see *Special Instructions*)

#### MASONRY

Plaster: } **EFF-STOP® Premium (ESPR00),**  
Tilt-up concrete: } **EFF-STOP® Select (ESSL00) or**  
Poured-in-place: } **FLEX-PRIME® Select (FPSL00)**  
Brick: }  
Smooth trowel: **SUPER-LOC® Premium (SLPR00)**  
Concrete block: **Smooth BLOCFIL™ Premium (SBPR00) or**  
**Smooth BLOCFIL™ Select (SBSL00)**

#### WOOD/SYNTHETIC WOOD-INTERIOR

Trim, doors: } **DECOPRIME™ (DCPR00),**  
Masonite: } **ULTRA-GRIP® Premium (UGPR00) or**  
Hardboard: } **ULTRA-GRIP® Select (UGSL00)**

**\*\*This product has been tested and certified by Coatings Research Group Inc., an international paint industry-organized ISO-accredited testing laboratory, to meet performance and environmental standards as shown on [www.greenwisepaint.com](http://www.greenwisepaint.com). Dunn-Edwards is a member of CRGI.**



THE #1 CHOICE OF  
PAINTING PROFESSIONALS®

# SPARTAWALL®

Low Odor | Zero VOC  
Interior Eggshell Paint  
SWLL30

## PRODUCT INFORMATION

**HEALTH & SAFETY CAUTIONS:** INHALATION OF SPRAY MIST OR SANDING DUST MAY BE HARMFUL. Use only with adequate ventilation. Avoid breathing vapors, spray mist and sanding dust. Wear NIOSH-approved N95 particulate filter mask when spraying or sanding. Avoid contact with skin and eyes. Do not ingest. Close container after each use. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water to drink – for emergency information, call 1-800-222-1222. If having difficulty breathing, move to fresh air. For eye contact, immediately flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water.

• KEEP OUT OF REACH OF CHILDREN •

Ingredient (CAS #): Water (7732-18-5); Copolymer Resin (Proprietary); Titanium Dioxide (13463-67-7); Nepheline Syenite (37244-96-5); Kaolin, Calcined (92704-41-1).

⚠ **WARNING:** Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)