



THE #1 CHOICE OF
PAINTING PROFESSIONALS®

VINYLASTIC® Plus

Interior Latex Wall Sealer VNPL00



DESCRIPTION: VINYLASTIC® Plus is a professional interior latex wall sealer that provides good hide and coverage. It is designed for use on new drywall in residential and commercial applications. Designed for use on Level 5 drywall finish.

PRODUCT INFORMATION

SOLVENT TYPE: Waterborne **RESIN TYPE:** Acrylic copolymer

FINISH (ASTM D 523): 1–2% on a 60° meter

COLORS: White. may be tinted with up to 2 fl. oz. of Dunn-Edwards ZTC Zero VOC colorant per gallon.

VISCOSITY@77°F/25°C (ASTM D 562): 93–103 KU

MAXIMUM VOC CONTENT 95 g/L (as supplied)	MAXIMUM RAVOC (Reactivity-Adjusted VOC) 50 g/L
--	--

SOLIDS BY VOLUME (ASTM D 2697) 27.8% ± 2%	SOLIDS BY WEIGHT 46.3% ± 2%
---	---------------------------------------

WEIGHT PER GALLON (ASTM D 1475): 11.19 lbs.

COMPOSITION BY WEIGHT

Pigment–38.9%		Vehicle–61.1%	
*Prime pigments	6.0	Acrylic resins	6.1
Reinforcing pigments	32.9	Water & additives	55.0

**Prime pigments include titanium dioxide (TiO₂), plus all other pigments directly adding to the hiding power of this paint.*

RECOMMENDED FILM THICKNESS PER COAT

Wet: 7.2 mils Dry: 2.0 mils

PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS
Approximately 150–200 sq. ft. per gallon, depending on surface conditions and application techniques.

THINNING RECOMMENDATION: This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.

AVERAGE DRY TIME@77°F/25°C (ASTM D 1640)

To touch: 30–60 minutes Recoat: 2–4 hours
Dry times and recoat times are temperature, humidity and film thickness dependent.

APPLICATION EQUIPMENT: Brush, roller, airless spray

PACKAGING: One-gallon, five-gallon containers

STORAGE: Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See *Paint Storage Best Practices* Technical Bulletin at dunnedwards.com for more information.

CLEANUP: Warm, soapy water

DISPOSAL: For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit www.dunnedwards.com. **Do not mix with other products.**

CONFORMS TO: ARB 2007 SCM & CALGreen 2013; LEED 2009 IEQ Credit 4.2

SAFETY DATA SHEET: Available at www.dunnedwards.com

SURFACE PREPARATION: All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

SPECIAL INSTRUCTIONS

- CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on “Surface Preparation Safety” or call EPA’s National Lead Information Hotline at 1-800-424-LEAD, or log onto www.epa.gov/lead/or/asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- New, untextured drywall is frequently covered with powdery and unstable joint compound. Remove excess dust before applying water-based sealers, such as VINYLASTIC Plus, to avoid adhesion problems.
- Not recommended for sealing beneath vinyl wallcovering.
- Allow all skim coats to cure for 3 days before sealing.
- Do not apply when the air or surface temperature is below 50°F.

USE AS A SEALER FOR

DRYWALL

Textured:	}	VINYLASTIC Plus
Untextured:		VINYLASTIC Plus
Skim-coated:		VINYLASTIC Plus (see Special Instructions)