



THE #1 CHOICE OF  
PAINTING PROFESSIONALS®

# W 5361

## Athletic Field Striping Paint

### W 5361



**DESCRIPTION:** **W 5361** is a premium latex flat paint designed for use on athletic fields and sports areas, including football fields, baseball diamonds, and soccer fields. **W 5361** produces a hard, breathable film that is resistant to the blistering effects of the sun. **W 5361** is easy to apply, safe, and dries quickly.

## PRODUCT INFORMATION

<b>SOLVENT TYPE:</b> Waterborne		<b>RESIN TYPE:</b> Acrylic copolymer	
<b>FINISH</b> (ASTM D 523): Flat: 1.5–3% on a 60° meter.			
<b>COLORS:</b> All colors must be special ordered.			
<b>VISCOSITY@77°F/25°C</b> (ASTM D 562): 102–110 KU			
<b>MAXIMUM VOC CONTENT</b> 2 g/L (as supplied)	<b>MAXIMUM RAVOC</b> (Reactivity-Adjusted VOC) 1 g/L		
<b>SOLIDS BY VOLUME</b> (ASTM D 2697) 37.5% ± 2%	<b>SOLIDS BY WEIGHT</b> 60.0% ± 2%		
<b>WEIGHT PER GALLON</b> (ASTM D 1475): 13.0 lbs.			
<b>COMPOSITION BY WEIGHT</b>			
<b>Pigment–55.2%</b>		<b>Vehicle–44.8%</b>	
*Prime pigments ..... 4.9	Vinyl acrylic resins ..... 3.7		
Reinforcing pigments ..... 50.3	Water & additives ..... 41.1		
<i>*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.</i>			
<b>RECOMMENDED FILM THICKNESS PER COAT</b>			
Wet: 5.3 mils		Dry: 2.0 mils	
<b>PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS</b> Approximately 250–300 sq. ft. per gallon, depending on surface conditions and application techniques.			
<b>THINNING RECOMMENDATION:</b> This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.			
<b>AVERAGE DRY TIME@77°F/25°C</b> (ASTM D 1640)			
To touch: 30–60 minutes		Recoat: 2–4 hours	
Dry times and recoat times are temperature, humidity and film thickness dependent.			
<b>APPLICATION EQUIPMENT:</b> Use a compressor type line marker or Bee-Liner Stripper.			
<b>PACKAGING:</b> Five-gallon containers			
<b>STORAGE:</b> Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See <b>Paint Storage Best Practices</b> Technical Bulletin at <a href="http://dunnedwards.com">dunnedwards.com</a> for more information.			
<b>CLEANUP:</b> Warm, soapy water			
<b>DISPOSAL:</b> For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit <a href="http://www.dunnedwards.com">www.dunnedwards.com</a> . <b>Do not mix with other products.</b>			
<b>CONFORMS TO:</b> ARB 2007 SCM & CALGreen 2013			
<b>SAFETY DATA SHEET:</b> Available at <a href="http://www.dunnedwards.com">www.dunnedwards.com</a>			
<b>SURFACE PREPARATION:</b> Remove all chalk and powder, leaving a clean surface to paint. It is not necessary to burn in the lines.			

### SPECIAL INSTRUCTIONS

- **CAUTION:** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. **EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH.** Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on “Surface Preparation Safety” or call EPA’s National Lead Information Hotline at 1-800-424-LEAD, or log onto [www.epa.gov/lead](http://www.epa.gov/lead) or/asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Do not apply when the air or surface temperature is below 50°F.