



THE #1 CHOICE OF
PAINTING PROFESSIONALS®

W 5361

Athletic Field Striping Paint

W 5361



DESCRIPTION: **W 5361** is a premium latex flat paint designed for use on athletic fields and sports areas, including football fields, baseball diamonds, and soccer fields. **W 5361** produces a hard, breathable film that is resistant to the blistering effects of the sun. **W 5361** is easy to apply, safe, and dries quickly.

PRODUCT INFORMATION

SOLVENT TYPE: Waterborne		RESIN TYPE: Acrylic copolymer	
FINISH (ASTM D 523): Flat: 1.5–3% on a 60° meter.			
COLORS: All colors must be special ordered.			
VISCOSITY@77°F/25°C (ASTM D 562): 102–110 KU			
MAXIMUM VOC CONTENT 2 g/L (as supplied)		MAXIMUM RAVOC (Reactivity-Adjusted VOC) 1 g/L	
SOLIDS BY VOLUME (ASTM D 2697) 37.5% ± 2%		SOLIDS BY WEIGHT 60.0% ± 2%	
WEIGHT PER GALLON (ASTM D 1475): 13.0 lbs.			
COMPOSITION BY WEIGHT			
Pigment—55.2%		Vehicle—44.8%	
*Prime pigments4.9		Vinyl acrylic resins3.7	
Reinforcing pigments.....50.3		Water & additives41.1	
<i>*Prime pigments include titanium dioxide (TiO₂), plus all other pigments directly adding to the hiding power of this paint.</i>			
RECOMMENDED FILM THICKNESS PER COAT			
Wet: 5.3 mils		Dry: 2.0 mils	
PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS			
Approximately 250–300 sq. ft. per gallon, depending on surface conditions and application techniques.			
THINNING RECOMMENDATION: This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.			
AVERAGE DRY TIME@77°F/25°C (ASTM D 1640)			
To touch: 30–60 minutes		Recoat: 2–4 hours	
Dry times and recoat times are temperature, humidity and film thickness dependent.			
APPLICATION EQUIPMENT: Use a compressor type line marker or Bee-Liner Stripper.			
PACKAGING: Five-gallon containers			
STORAGE: Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See <i>Paint Storage Best Practices</i> Technical Bulletin at dunnedwards.com for more information.			
CLEANUP: Warm, soapy water			
DISPOSAL: For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit www.dunnedwards.com . Do not mix with other products.			
CONFORMS TO: ARB 2007 SCM & CALGreen 2016			
SAFETY DATA SHEET: Available at www.dunnedwards.com			
SURFACE PREPARATION: Remove all chalk and powder, leaving a clean surface to paint. It is not necessary to burn in the lines.			

SPECIAL INSTRUCTIONS

- **CAUTION!** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Wear a NIOSH-approved N95 particulate filter mask to avoid breathing dust. Use a HEPA vacuum for cleanup, and finish by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call U.S. EPA's lead hotline at 1-800-424-LEAD, or visit www.epa.gov/lead or /asbestos, or contact your state or local Health Agency.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- Do not apply when the air or surface temperature is below 50°F.

PRIMERS

METAL

- Ferrous: **BLOC-RUST® Premium (BRPR00)** or **ENDURAPRIME™ Metal Primer (ENPR00)**
- Non-ferrous: **ULTRASHIELD® Galvanized Metal Primer (ULGM00)** or **BLOC-RUST® Premium (BRPR00)**
- Galvanized steel: **ULTRASHIELD® Galvanized Metal Primer (ULGM00)** or ***ULTRA-GRIP® Premium (UGPR00)**

**for incidental use on galvanized*

HEALTH & SAFETY: CAUTIONS! INHALATION OF SPRAY MIST OR SANDING DUST MAY BE HARMFUL. Use only with adequate ventilation. Avoid breathing vapors, spray mist and sanding dust. Wear NIOSH-approved N95 particulate filter mask when spraying or sanding. Avoid contact with skin and eyes. Do not ingest. Close container after each use. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water to drink – for emergency information, call 1-800-222-1222. If having difficulty breathing, move to fresh air. For eye contact, immediately flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water.

• KEEP OUT OF REACH OF CHILDREN •

Limestone (1317-65-8); Water (7732-18-5); Titanium Dioxide (13463-67-7); Copolymer Resin (Proprietary); Cristobalite (14464-46-1); Quartz (14808-60-7).

⚠ **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov