THE #1 CHOICE OF PAINTING PROFESSIONALS®

QUIK-WALL®
Interior
Washable Latex Flat Paint
W 6401V

DESCRIPTION: QUIK-WALL® is a quality heavy-bodied washable flat wall paint that offers good hide and very good touch-up properties. It dries fast and is self-priming on new drywall. This is a concentrated formulation that requires thinning. **QUIK-WALL** is designed for use on interior walls, ceilings, and other properly prepared and primed new surfaces.

PRODUCT INFORMATION

SOLVENT TYPE: Waterborne | **RESIN TYPE:** Acrylic copolymer

FINISH (ASTM D 523)**:** Flat: 1.0% on a 60° meter; <1.5% on an 85° meter

COLORS: Stock colors: White, Cottage White, Navajo White, Pearl White, and Swiss Coffee. Other colors can be special ordered or store mixed.

VISCOSITY@77°F/25°C (ASTM D 562)**:** 134–140 KU

MAXIMUM VOC CONTENT	**MAXIMUM RAVOC** (Reactivity-Adjusted VOC)
15 g/L (as supplied)	10 g/L

SOLIDS BY VOLUME (ASTM D 2697)	**SOLIDS BY WEIGHT**
43.6% ± 2%	63.7% ± 2%

WEIGHT PER GALLON (ASTM D 1475)**:** 12.95 lbs.

COMPOSITION BY WEIGHT

Pigment–50.8%		**Vehicle–49.2%**	
*Prime pigments	11.3	Modified copolymer resins	10.3
Reinforcing pigments	39.5	Water & additives	38.9

**Prime pigments include titanium dioxide (TiO_2), plus all other pigments directly adding to the hiding power of this paint.*

RECOMMENDED FILM THICKNESS PER COAT
Wet: 4.6 mils Dry: 2.0 mils

PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS
Approximately 275–325 sq. ft. per gallon, depending on surface conditions and application techniques.

THINNING RECOMMENDATION: Brush or roller application: Up to 1 gallon of water per five gallons of paint. Spray application: Up to 2 gallons of water per five gallons of paint.

AVERAGE DRY TIME@77°F/25°C (ASTM D 1640)
To touch: 30–60 minutes Recoat: 2–4 hours

APPLICATION EQUIPMENT: Brush, roller, airless spray

PACKAGING: Five-gallon containers

STORAGE: Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.

CLEANUP: Warm, soapy water

DISPOSAL: For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit www.dunnedwards.com. **Do not mix with other products**.

CONFORMS TO: LEED 2009 IEQ Credit 4.2: Paints & Coatings; Green Seal Standard GS-11 (1st Edition)

MATERIAL SAFETY DATA SHEET: Available at www.dunnedwards.com

SURFACE PREPARATION: All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

SPECIAL INSTRUCTIONS

- CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or log onto www. epa.gov/lead or/asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- **QUIK-WALL®** is a concentrate and needs to be reduced with water prior to application (see Thinning Recommendations).
- When touching up **QUIK-WALL®**, use the same application method originally used and use paint from the same batch. If spray touch-up is not practical, use a good quality 1/2″ nap synthetic roller for best sheen uniformity, especially on smooth walls. Apply a full coat at original application viscosity. Vertical strokes are preferred over horizontal. Avoid feathering (excessive rolling or brushing) into the original painted areas around the touch-up. For more information, see Dunn-Edwards brochure on "Quality Touch-Up."
- Do not apply when the air or surface temperature is below 50°F.

PRIMERS

DRYWALL
Textured:
Untextured:
Skin-coated: } **Self-priming**

MASONRY
Plaster:
Tilt-up concrete:
Poured-in-place:
Brick: } **SUPER-LOC® Premium (SLPRA00/SLPRB00)**, **EFF-STOP® Premium (ESPR00)** or **EFF-STOP® Select (ESSL00)**
Concrete block: **Medium BLOCFIL Premium (MBPR00)**, **Smooth BLOCFIL Premium (SBPR00)** or **Smooth BLOCFIL Select (SBSL00)**
Smooth trowel: **SUPER-LOC® Premium (SLPRA00/SLPRB00)** or **ENDURASEAL® (W 360)**

WOOD
Doors, trim: **INTER-KOTE® Premium (IKPR00)** or **ULTRA-GRIP® Premium (UGPR00)**

SYNTHETIC WOOD
Masonite: **INTER-KOTE® Premium (IKPR00)**
Hardboard: **ULTRA-GRIP® Premium (UGPR00)**

METAL
Ferrous: **ULTRA-GRIP® Premium (UGPR00)** – *INTERIOR ONLY*, **BLOC-RUST® Premium (BRPR00-1)** or **GALV-ALUM™ Premium (GAPR00)**
Non-ferrous: **GALV-ALUM™ Premium (GAPR00)** or **ULTRA-GRIP® Premium (UGPR00)**

GALV-ALUM™ is a trademark of BIEC International, Inc. used under license by Dunn-Edwards Corporation.