

# SAFETY DATA SHEET

DCPR00 DECOPRIME INTERIOR CABINET, DOOR & TRIM PRIMER

SDS DATE: 12/07/2020

---

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

---

**PRODUCT IDENTIFICATION:**  
DCPR00 DECOPRIME INTERIOR CABINET, DOOR & TRIM PRIMER

**MANUFACTURER:** DUNN-EDWARDS CORPORATION  
4885 EAST 52<sup>ND</sup> PLACE  
LOS ANGELES, CA 90058-5507

**PRODUCT TYPE:** WATERBORNE PAINT  
**RECOMMENDED USE:** ARCHITECTURAL COATING

**EMERGENCY PHONE:** 1-800-222-1222  
**OTHER CALLS:** (323) 826-2663  
**FAX NUMBER:** (323) 771-1611

**HMIS CODES:**    H     F     R     PP  
                      0     0     0     E



THE #1 CHOICE OF  
PAINTING PROFESSIONALS®

---

## SECTION 2: HAZARDS IDENTIFICATION

---

**GHS CLASSIFICATION:** NOT A HAZARDOUS SUBSTANCE OR MIXTURE.

**GHS LABEL ELEMENTS:** [NOTE: THIS CONSUMER PRODUCT IS EXEMPT FROM OSHA GHS-HCS LABELING REQUIREMENTS.]

**SIGNAL WORD:** (NONE REQUIRED)      **HAZARD STATEMENT:** (NONE REQUIRED)

**PICTOGRAM:** (NONE REQUIRED)

**PRECAUTIONARY STATEMENTS:**

**PREVENTION:** DO NOT INGEST. USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPORS, SPRAY MIST AND SANDING DUST. WEAR APPROPRIATE NIOSH-APPROVED RESPIRATORY PROTECTION WHEN SPRAYING OR SANDING. AVOID CONTACT WITH SKIN AND EYES. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN.

**RESPONSE:** CLEAN UP SPILLS WITH INERT ABSORBENT MATERIAL, SUCH AS CLAY GRANULES, PAPER OR CLOTH WIPES. ALLOW TO DRY BEFORE DISPOSAL.

**STORAGE & DISPOSAL:** KEEP BETWEEN 40°F AND 110°F AT ALL TIMES. DISPOSE OF CONTAINER AND CONTENTS IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

**HAZARDS NOT OTHERWISE CLASSIFIED:** NONE.

---

## SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

---

**HAZARDOUS INGREDIENTS:**

CHEMICAL NAME	COMMON NAME / SYNONYMS	CAS NUMBER	CONCENTRATION (%WT)
---------------	------------------------	------------	---------------------

NO REPORTABLE HAZARDOUS INGREDIENTS.

NOTE: EXPOSURES TO POSSIBLE HAZARDOUS INGREDIENTS BELOW REPORTING THRESHOLDS CAN BE REDUCED OR AVOIDED BY FOLLOWING RECOMMENDED PROCEDURES FOR SAFE HANDLING, STORAGE, DISPOSAL, AND USE.

SEE SECTION 11 (TOXICOLOGICAL INFORMATION) FOR POSSIBLE HAZARDOUS BY-PRODUCTS.

# SAFETY DATA SHEET

DCPR00 DECOPRIME INTERIOR CABINET, DOOR & TRIM PRIMER

SDS DATE: 12/07/2020

---

## SECTION 4: FIRST-AID MEASURES

---

EYES: FLUSH EYES WITH FRESH WATER FOR AT LEAST 15 MINUTES.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: HAVE VICTIM DRINK 1 OR 2 GLASSES OF WATER TO ENSURE DILUTION.

INHALATION: MOVE VICTIM TO FRESH AIR.

MOST IMPORTANT SYMPTOMS AND EFFECTS: MAY CAUSE MILD IRRITATION TO SKIN AND EYES, GASTROINTESTINAL AND RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND HEADACHE POSSIBLE.

NOTES TO FIRST AID PROVIDERS: CALL FOR MEDICAL ASSISTANCE IF SYMPTOMS PERSIST.

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

SUITABLE EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

UNUSUAL FIRE AND EXPLOSION HAZARDS: LIQUID MATERIAL IS NON-COMBUSTIBLE, BUT DRIED FILMS ARE CAPABLE OF SUPPORTING COMBUSTION WHEN IN CONTACT WITH OPEN FLAMES. CLOSED CONTAINERS CAN DEVELOP INTERNAL PRESSURE AND MAY RUPTURE WHEN SUBJECTED TO EXTREME HEAT.

HAZARDOUS COMBUSTION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

SPECIAL EQUIPMENT & PRECAUTIONS: USE SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES. OBSERVE RECOMMENDED PROCEDURES FOR HANDLING ORDINARY COMBUSTIBLE MATERIALS.

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, EMERGENCY PROCEDURES: WEAR WATERPROOF GLOVES TO AVOID SKIN CONTACT. KEEP CHILDREN AND PETS AWAY FROM SPILLED LIQUID. PREVENT LIQUID FROM ENTERING DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP: DIKE SPILLED LIQUID WITH INERT MATERIAL, SUCH AS CLAY GRANULES. SCOOP UP EXCESS LIQUID AND POUR INTO CONTAINER. USE PAPER OR CLOTH WIPES TO CLEAN UP SMALL SPILLS. ALLOW TO DRY BEFORE DISPOSAL.

---

## SECTION 7: HANDLING AND STORAGE

---

SAFE HANDLING PRECAUTIONS: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STACK CONTAINERS MORE THAN THREE HIGH. SECURE LOADS AGAINST SHIFTING DURING TRANSPORTATION. USE ONLY AN APPROPRIATE TOOL TO OPEN CONTAINERS.

SAFE STORAGE CONDITIONS: STORE IN COOL, WELL-VENTILATED AREA. MAINTAIN TEMPERATURE BETWEEN 40°F AND 110°F. AVOID EXPOSURE TO DIRECT SUNLIGHT, HEAT OR FLAME. INSPECT CONTAINERS FOR LEAKS PERIODICALLY. ROTATE STOCK, USE OLDER MATERIAL FIRST.

INCOMPATIBILITIES: DO NOT HANDLE OR STORE NEAR WATER-REACTIVE MATERIALS, STRONG OXIDIZERS, ACIDS OR ALKALIS.

# SAFETY DATA SHEET

DCPR00 DECOPRIME INTERIOR CABINET, DOOR & TRIM PRIMER

SDS DATE: 12/07/2020

---

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

---

HAZARDOUS INGREDIENTS	CAS NUMBER	%WT	ACGIH				OSHA EXPOSURE LIMITS		VAPOR PRESS mmHg @ TEMP
			TLV/TWA	PPM	TWA	PPM	MG/M <sup>3</sup>	PPM	

NO REPORTABLE HAZARDOUS INGREDIENTS.

**ENGINEERING CONTROLS:** USE SIGNS OR BARRIERS TO RESTRICT ACCESS TO PAINTING WORK AREA.

**VENTILATION :** NORMAL AIR CIRCULATION SHOULD BE SUFFICIENT; OTHERWISE, USE PORTABLE FANS. ENSURE ADEQUATE VENTILATION DURING APPLICATION, DRYING AND CURING OF PAINT.

**RESPIRATORY PROTECTION:** FOR SPRAY APPLICATION, USE A NIOSH-APPROVED PARTICULATE FILTER MASK (RATED N95 OR HIGHER) TO AVOID BREATHING SPRAY MIST. EXPOSED PERSONS WITH ALLERGIES OR ASTHMA MAY NEED AN ORGANIC VAPOR/PARTICULATE RESPIRATOR (NIOSH/MSHA TC 23C OR EQUIVALENT).

WHEN SANDING, SCRAPING, OR ENGAGING IN ANY ACTIVITY THAT GENERATES AIRBORNE NUISANCE DUST, WEAR A NIOSH-APPROVED PARTICULATE FILTER MASK (RATED N95 OR HIGHER) TO AVOID BREATHING DUST. FINISH CLEANUP BY WATER-WASHING ALL SURFACES TO REMOVE DUST RESIDUE.

**EYE PROTECTION:** USE SAFETY GLASSES, GOGGLES, OR FACE SHIELD TO PROTECT EYES.

**SKIN PROTECTION:** USE WATERPROOF GLOVES (LATEX, VINYL, RUBBER, OR NEOPRENE) TO AVOID SKIN CONTACT.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** WATERPROOF HEADCOVERING AND GENERAL PROTECTIVE CLOTHING ARE RECOMMENDED FOR PROTECTION AS NECESSARY.

**WORK HYGIENIC PRACTICES:** WASH HANDS AND FACE BEFORE EATING OR DRINKING.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE:	OPAQUE LIQUID DISPERSION	VAPOR PRESSURE:	SAME AS WATER VAPOR	
ODOR:	VERY MILD ODOR	VAPOR DENSITY:	SAME AS WATER VAPOR	
ODOR THRESHOLD:	(NO INFORMATION AVAILABLE)	SPECIFIC GRAVITY:	~1.3 (H <sub>2</sub> O = 1)	
pH AS SUPPLIED:	~8.5	SOLUBILITY IN WATER:	PARTLY SOLUBLE	
FREEZING POINT:	0° C / 32° F	PARTITION COEFFICIENT:	(NO INFORMATION AVAILABLE)	
BOILING POINT:	100° C / 212° F	AUTO-IGNITION TEMP:	(NOT APPLICABLE)	
FLASH POINT:	(NOT APPLICABLE)	DECOMPOSTION TEMP:	(NO INFORMATION AVAILABLE)	
EVAPORATION RATE:	SAME AS WATER	VISCOSITY:	98 – 106 KU	
FLAMMABILITY:	(NOT APPLICABLE)	PERCENT SOLIDS:	BY VOL: ~38%	BY WT: ~53%
UPPER EXPLOSIVE LIMIT:	(NOT APPLICABLE)	PERCENT VOLATILE:	BY VOL: ~62%	BY WT: ~47%
LOWER EXPLOSIVE LIMIT:	(NOT APPLICABLE)			

# SAFETY DATA SHEET

DCPR00 DECOPRIME INTERIOR CABINET, DOOR & TRIM PRIMER

SDS DATE: 12/07/2020

---

## SECTION 10: STABILITY AND REACTIVITY

---

REACTIVITY: REACTIVITY NOT KNOWN TO OCCUR UNDER NORMAL CONDITIONS.

CHEMICAL STABILITY: STABLE UNDER NORMAL CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS: POLYMERIZATION WILL NOT OCCUR.

CONDITIONS TO AVOID: AVOID STORAGE AT TEMPERATURES BELOW 40° F OR ABOVE 110° F.

INCOMPATIBLE MATERIALS: AVOID WATER-REACTIVE MATERIALS, STRONG OXIDIZERS, ACIDS AND ALKALIS.

HAZARDOUS DECOMPOSITION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

LIKELY ROUTES OF EXPOSURE: INHALATION, INGESTION, EYE AND SKIN CONTACT

SYMPTOMS OF OVEREXPOSURE: MAY CAUSE MILD IRRITATION TO SKIN AND EYES, GASTROINTESTINAL AND RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND HEADACHE POSSIBLE.

DELAYED OR CHRONIC EFFECTS: AVAILABLE INFORMATION PROVIDES NO EVIDENCE OF DELAYED OR CHRONIC HEALTH EFFECTS ASSOCIATED WITH EXPOSURE TO THIS PRODUCT DURING NORMAL USE WITH RECOMMENDED PERSONAL PROTECTION AS NEEDED.

NUMERICAL MEASURES OF TOXICITY: (NO INFORMATION AVAILABLE)

CARCINOGENICITY (WHOLE PRODUCT): ACGIH? NO. IARC? NO. NIOSH? NO. NTP? NO. OSHA? NO.

HAZARDOUS BY-PRODUCTS: SPRAY APPLICATION OF THIS PRODUCT CAN GENERATE SPRAY MIST, WHICH MAY BE HARMFUL IF INHALED. RESPIRATORY IRRITATION AND SHORTNESS OF BREATH POSSIBLE. RISK DEPENDS ON LEVEL AND DURATION OF EXPOSURE.

SANDING, SCRAPING, OR OTHERWISE DISTURBING THE DRY FILM OF THIS PRODUCT CAN GENERATE AIRBORNE NUISANCE DUST, WHICH MAY BE HARMFUL IF INHALED. RESPIRATORY IRRITATION AND SHORTNESS OF BREATH POSSIBLE. RISK DEPENDS ON LEVEL AND DURATION OF EXPOSURE.

SEE SECTION 8 (EXPOSURE CONTROLS / PERSONAL PROTECTION) FOR INFORMATION ON RESPIRATORY PROTECTION WHEN SPRAYING OR SANDING.

NOTE: SPRAY MIST OR SANDING DUST MAY CONTAIN TITANIUM DIOXIDE PIGMENT PARTICLES BOUND IN THE RESINOUS MATRIX OF (1) PAINT DROPLETS THAT MAKE UP SPRAY MIST OR (2) PAINT FRAGMENTS THAT MAKE UP SANDING DUST. TITANIUM DIOXIDE, IN THE FORM OF AIRBORNE, UNBOUND PARTICLES OF RESPIRABLE SIZE, HAS BEEN CLASSIFIED BY IARC AS GROUP 2B: POSSIBLY CARCINOGENIC TO HUMANS, BASED ON TWO LABORATORY WHITE RAT INHALATION EXPOSURE STUDIES, IN WHICH LUNG OVERLOAD CONDITIONS RESULTED IN TUMOR FORMATION. THE IARC MONOGRAPH ON TITANIUM DIOXIDE, HOWEVER, STATES AT THE CONCLUSION OF ITS SUMMARY CHAPTER: "NO SIGNIFICANT EXPOSURE TO PRIMARY PARTICLES OF TITANIUM DIOXIDE IS THOUGHT TO OCCUR DURING THE USE OF PRODUCTS IN WHICH TITANIUM DIOXIDE IS BOUND TO OTHER MATERIALS, SUCH AS IN PAINTS." ALSO, MULTIPLE EPIDEMIOLOGICAL STUDIES OF TITANIUM DIOXIDE PRODUCTION WORKERS WITH LONG-TERM OCCUPATIONAL EXPOSURE TO AIRBORNE TITANIUM DIOXIDE DUST FOUND NO RELIABLE CORRELATION BETWEEN EXPOSURE AND INCIDENCE OF LUNG CANCER OR OTHER CHRONIC LUNG DISEASES. SCIENTISTS AT MAJOR SUPPLIERS OF TITANIUM DIOXIDE PIGMENT TO DUNN-EDWARDS HAVE EACH PERFORMED AN INDEPENDENT GHS HAZARD CLASSIFICATION OF TITANIUM DIOXIDE PIGMENT AND EACH CONCLUDED THAT TITANIUM DIOXIDE PIGMENT IS "NOT A HAZARDOUS SUBSTANCE OR MIXTURE," BASED ON THE WEIGHT OF SCIENTIFIC EVIDENCE.

SPRAY MIST OR SANDING DUST MAY ALSO CONTAIN QUARTZ AND/OR CRISTOBALITE PARTICLES BOUND IN THE RESINOUS MATRIX OF (1) PAINT DROPLETS THAT MAKE UP SPRAY MIST OR (2) PAINT FRAGMENTS THAT MAKE UP SANDING DUST. QUARTZ AND CRISTOBALITE ARE TWO VARIETIES OF CRYSTALLINE SILICA, WHICH, IN THE FORM OF AIRBORNE, UNBOUND PARTICLES OF RESPIRABLE SIZE, HAS BEEN CLASSIFIED BY IARC AS GROUP 1: CARCINOGENIC TO HUMANS, BASED ON EVIDENCE THAT LONG-TERM OCCUPATIONAL EXPOSURE TO FREE CRYSTALLINE SILICA DUST CAN CAUSE SILICOSIS, A CHRONIC LUNG DISEASE THAT MAY PROGRESS TO LUNG CANCER. EXPOSURE TO FREE CRYSTALLINE SILICA DUST COMMONLY OCCURS IN WORK WITH ROCK, STONE, GRAVEL, SAND, SOIL, CONCRETE, AND MASONRY.

# SAFETY DATA SHEET

DCPR00 DECOPRIME INTERIOR CABINET, DOOR & TRIM PRIMER

SDS DATE: 12/07/2020

---

## SECTION 12: ECOLOGICAL INFORMATION

---

ECOLOGICAL INFORMATION: (NO INFORMATION AVAILABLE)

---

## SECTION 13: DISPOSAL CONSIDERATIONS

---

WASTE DISPOSAL METHOD: COLLECT SPILLED MATERIAL, USED ABSORBENT MATERIAL AND WIPES INTO A SUITABLE CONTAINER AND DISPOSE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS. DRY, EMPTY CONTAINERS MAY BE RECYCLED OR DISPOSED OF AS ORDINARY TRASH.

RCRA HAZARD CLASS: NON-HAZARDOUS

---

## SECTION 14: TRANSPORT INFORMATION

---

THIS MATERIAL IS NOT SUBJECT TO DOT, IATA/ICAO, OR IMO/IMDG TRANSPORTATION REGULATIONS. ACCEPTABLE FOR AIR TRANSPORT AS NON-HAZARDOUS GOODS.

UN NUMBER: (NOT APPLICABLE) UN PROPER SHIPPING NAME: (NOT APPLICABLE)

TRANSPORT HAZARD CLASS: (NOT APPLICABLE) PACKING GROUP: (NOT APPLICABLE)

ENVIRONMENTAL HAZARDS: (NOT APPLICABLE) TRANSPORT IN BULK: (NOT APPLICABLE)

SPECIAL PRECAUTIONS: FOLLOW RECOMMENDED PROCEDURES FOR SAFE HANDLING AND STORAGE.

---

## SECTION 15: REGULATORY INFORMATION

---

U.S. FEDERAL REGULATIONS:

TSCA: ALL COMPONENTS ARE LISTED IN TSCA INVENTORY OR EXEMPT.

CERCLA: NOT LISTED AS A HAZARDOUS SUBSTANCE.

SARA TITLE III: NOT LISTED AS A HAZARDOUS SUBSTANCE.

311/312 HAZARD CATEGORIES: (NOT APPLICABLE)

313 REPORTABLE INGREDIENTS: (NOT APPLICABLE)

STATE REGULATIONS: CALIFORNIA PROPOSITION 65 NOTICE:

 **WARNING!** CANCER AND REPRODUCTIVE HARM – [WWW.P65WARNINGS.CA.GOV](http://WWW.P65WARNINGS.CA.GOV)

---

## SECTION 16: OTHER INFORMATION

---

DATE OF PREPARATION: DECEMBER 7, 2020

PREPARER INFORMATION: DUNN-EDWARDS CORPORATION  
ENVIRONMENTAL AFFAIRS DEPARTMENT  
PHONE: (323) 826-2663

DISCLAIMER: THE INFORMATION CONVEYED ABOVE, ALTHOUGH OBTAINED FROM SOURCES WE CONSIDER RELIABLE, IS FURNISHED BY DUNN-EDWARDS CORPORATION WITHOUT ANY WARRANTY (WHETHER EXPRESS OR IMPLIED) AS TO ITS ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR NEEDS OR CIRCUMSTANCES.