



THE #1 CHOICE OF
PAINTING PROFESSIONALS®

SAFETY DATA SHEET

SDS FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

The following Safety Data Sheet (SDS) is being provided pursuant to requirements of the Fed/OSHA (29 CFR 1910.1200) and Cal/OSHA (8 CCR 5194) Hazard Communication Standards. The health and hazards information given here is based on data believed to be accurate by Dunn-Edwards Corporation; we do not, however, assume any liability for the accuracy or completeness of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that may exist. All persons intending to rely on any recommendation, or to use any technique, equipment, or material mentioned should first satisfy themselves that they can meet all applicable safety and health standards.

The following SDS supersedes any previously issued SDS for each product covered. The reader is advised to destroy any obsolete SDS and refer only to this SDS. As permitted by OSHA, each SDS may apply to a class of products which have similar hazards and contents.

Products covered by this SDS are listed below:

ACBL10-0: ACRI-BUILD Flat	ESPR00-1: EFF-STOP Premium
ACHS10-0: ACRI-HUES Flat	ESSL00-0: EFF-STOP Select
ACHS30-0: ACRI-HUES Eggshell	EVER10-0: EVEREST Flat
ACHS50-0: ACRI-HUES Semi-Gloss	EVER20-0: EVEREST Velvet
ACWC10-0: ACRI-WALL Flat Concentrate	EVER30-0: EVEREST Eggshell
ACWL10-0: ACRI-WALL Flat Ready-To-Use	EVER50-0: EVEREST Semi-Gloss
ACWL30-0: ACRI-WALL Eggshell	EVSH10-2: EVERSIELD Flat
ACWL50-0: ACRI-WALL Semi-Gloss	EVSH10-3: EVERSIELD Flat
AQUA10-1: AQUAFALL Flat	EVSH20-2: EVERSIELD Velvet
AQUA30-1: AQUAFALL Eggshell	EVSH20-3: EVERSIELD Velvet
AQUA50-1: AQUAFALL Semi-Gloss	EVSH30-2: EVERSIELD Eggshell
ASHL30-0: ARISTOSHIELD Eggshell	EVSH30-3: EVERSIELD Eggshell
ASHL40-0: ARISTOSHIELD Low Sheen	EVSH40-2: EVERSIELD Low-Sheen
ASHL50-0: ARISTOSHIELD Semi-Gloss	EVSH40-3: EVERSIELD Low-Sheen
ASHL70-0: ARISTOSHIELD High Gloss	EVSH50-2: EVERSIELD Semi-Gloss
AWLL50-0: ARISTOWALL Semi-Gloss	EVSH50-3: EVERSIELD Semi-Gloss
AWLL60-0: ARISTOWALL Gloss	EVSH60-2: EVERSIELD Gloss
BIPR00-1: BLOCK-IT Premium	EVSH60-3: EVERSIELD Gloss
BRPR00-2-RO: BLOC-RUST Premium, Red Oxide	EZPR00-1: EZ-PRIME Premium
BRPR00-2-WH: BLOC-RUST Premium, White	FPSL00-1: FLEX-PRIME Select
DURA50-0: DURAFLO Semi-Gloss	FTXS10-0: FLEX-TEX Smooth
DURA50-1: DURAFLO Semi-Gloss	IKPR00-1: INTER-KOTE Premium Zero VOC
DURA60-0: DURAFLO Gloss	PMCE10-0: CONTRACTOR'S EDGE Flat
DURA60-1: DURAFLO Gloss	PMCE30-0: CONTRACTOR'S EDGE Eggshell
ENCT30-0: ENDURA-COAT Eggshell	PMCE50-0: CONTRACTOR'S EDGE Semi-Gloss
ENCT50-0: ENDURA-COAT Semi-Gloss	PRWL00-0: PREP-WALL Drywall Surface Conditioner
ENCT60-0: ENDURA-COAT Gloss	QKWL10-0: QUIK-WALL Flat
ENPR00-0-GR: ENDURAPRIME, Gray	
ENPX50-0: ENDURACAT Semi-Gloss	

continued

SDS FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS *continued*

SBPR00-0: Smooth BLOCFIL Premium
SBSL00-1: Smooth BLOCFIL Select
SFSL00-1: SURFACO Select
SLPR00-2: SUPER-LOC Premium
SPMA10-1: SUPREMA Flat
SPMA20-1: SUPREMA Velvet
SPMA30-0: SUPREMA Eggshell
SPMA40-0: SUPREMA Low Sheen
SPMA50-0: SUPREMA Semi-Gloss
SSHL10-0: SPARTASHIELD Flat
SSHL20-0: SPARTASHIELD Velvet
SSHL30-0: SPARTASHIELD Eggshell
SSHL40-0: SPARTASHIELD Low Sheen
SSHL50-1: SPARTASHIELD Semi-Gloss
SSHL60-1: SPARTASHIELD Gloss
SSHV10-0: SPARTASHIELD VA Flat
SWLL10-0: SPARTAWALL Flat
SWLL20-1: SPARTAWALL Velvet
SWLL30-1: SPARTAWALL Eggshell
SWLL40-1: SPARTAWALL Low Sheen
SWLL50-1: SPARTAWALL Semi-Gloss
SWLR10-0: SUPER-WALL Flat Ready-To-Use
SZRO10-0: SPARTAZERO Flat
SZRO20-0: SPARTAZERO Velvet
SZRO30-0: SPARTAZERO Eggshell
SZRO40-0: SPARTAZERO Low Sheen

SZRO50-0: SPARTAZERO Semi-Gloss
UGPR00-1: ULTRA-GRIP Premium
UGSL00-1: ULTRA-GRIP Select Zero VOC
ULDM00-0-GR: ULTRASHIELD DTM Gray Primer
ULDM50-0: ULTRASHIELD DTM Semi-Gloss Paint
ULGM00-0: ULTRASHIELD Galvanized Metal Primer
ULMS00-0: ULTRASHIELD Multi-Surface Primer
ULSB10-0: ULTRA-SCRUB Flat
ULSH40-0: ULTRASHIELD Low Sheen Paint
ULSH60-0: ULTRASHIELD Gloss Paint
VNPL00-0: VINYLASTIC Plus
VNPR00-1: VINYLASTIC Premium Ultra-Low VOC
VNSL00-1: VINYLASTIC Select Zero VOC
W 350: Interior W/B Acrylic Clear Finish
W 360V: ENDURASEAL
W 370: ENDURAWALL
W 615: ACOUSTIKOTE
W 2456V: Latex Roof Coating
W 5361: Athletic Field Striping Paint
W 6139: Acrylic Elastomeric Coating AZ
W 6160E: VERSAGLO
W 6220E: VERSAGLOSS
W 6230E: VERSAWALL
W 6240: VERSAFLAT
W 6250E: VERSASATIN

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 09/23/2019

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION:
SEE COVER PAGE FOR LIST OF PRODUCTS COVERED

MANUFACTURER: DUNN-EDWARDS CORPORATION
4885 EAST 52ND PLACE
LOS ANGELES, CA 90058-5507

PRODUCT TYPE: WATERBORNE PAINT
RECOMMENDED USE: ARCHITECTURAL COATING

EMERGENCY PHONE: 1-800-222-1222
OTHER CALLS: (323) 826-2663
FAX NUMBER: (323) 771-1611

HMIS CODES: H F R PP
0 0 0 E



THE #1 CHOICE OF
PAINTING PROFESSIONALS®

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION: NOT A HAZARDOUS SUBSTANCE OR MIXTURE

GHS LABEL ELEMENTS: [NOTE: THIS CONSUMER PRODUCT IS EXEMPT FROM OSHA GHS-HCS LABELING REQUIREMENTS.]

SIGNAL WORD: (NONE REQUIRED) HAZARD STATEMENT: (NONE REQUIRED)

PICTOGRAM: (NONE REQUIRED)

PRECAUTIONARY STATEMENTS:

PREVENTION: DO NOT INGEST. USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPORS, SPRAY MIST AND SANDING DUST. WEAR APPROPRIATE NIOSH-APPROVED RESPIRATORY PROTECTION WHEN SPRAYING OR SANDING. AVOID CONTACT WITH SKIN AND EYES. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN.

RESPONSE: CLEAN UP SPILLS WITH INERT ABSORBENT MATERIAL, SUCH AS CLAY GRANULES, PAPER OR CLOTH WIPES. ALLOW TO DRY BEFORE DISPOSAL.

STORAGE & DISPOSAL: KEEP BETWEEN 40°F AND 110°F AT ALL TIMES. DISPOSE OF CONTAINER AND CONTENTS IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

HAZARDS NOT OTHERWISE CLASSIFIED: NONE.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS:

CHEMICAL NAME	COMMON NAME / SYNONYMS	CAS NUMBER	CONCENTRATION (%WT)
---------------	------------------------	------------	---------------------

NO REPORTABLE HAZARDOUS INGREDIENTS.

NOTE: EXPOSURES TO POSSIBLE HAZARDOUS INGREDIENTS BELOW REPORTING THRESHOLDS CAN BE MINIMIZED OR AVOIDED BY FOLLOWING RECOMMENDED PROCEDURES FOR SAFE HANDLING, STORAGE, DISPOSAL, AND USE.

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 09/23/2019

SECTION 4: FIRST-AID MEASURES

EYES: FLUSH EYES WITH FRESH WATER FOR AT LEAST 15 MINUTES.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: HAVE VICTIM DRINK 1 OR 2 GLASSES OF WATER TO ENSURE DILUTION.

INHALATION: MOVE VICTIM TO FRESH AIR.

MOST IMPORTANT SYMPTOMS AND EFFECTS: MAY CAUSE MILD IRRITATION TO SKIN AND EYES, GASTROINTESTINAL AND RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND HEADACHE POSSIBLE.

NOTES TO FIRST AID PROVIDERS: CALL FOR MEDICAL ASSISTANCE IF SYMPTOMS PERSIST.

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

UNUSUAL FIRE AND EXPLOSION HAZARDS: LIQUID MATERIAL IS NON-COMBUSTIBLE, BUT DRIED FILMS ARE CAPABLE OF SUPPORTING COMBUSTION WHEN IN CONTACT WITH OPEN FLAMES. CLOSED CONTAINERS CAN DEVELOP INTERNAL PRESSURE AND MAY RUPTURE WHEN SUBJECTED TO EXTREME HEAT.

HAZARDOUS COMBUSTION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

SPECIAL EQUIPMENT & PRECAUTIONS: USE SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES. OBSERVE RECOMMENDED PROCEDURES FOR HANDLING ORDINARY COMBUSTIBLE MATERIALS.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, EMERGENCY PROCEDURES: WEAR WATERPROOF GLOVES TO AVOID SKIN CONTACT. KEEP CHILDREN AND PETS AWAY FROM SPILLED LIQUID. PREVENT LIQUID FROM ENTERING DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP: DIKE SPILLED LIQUID WITH INERT MATERIAL, SUCH AS CLAY GRANULES. SCOOP UP EXCESS LIQUID AND POUR INTO CONTAINER. USE PAPER OR CLOTH WIPES TO CLEAN UP SMALL SPILLS. ALLOW TO DRY BEFORE DISPOSAL.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PRECAUTIONS: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STACK CONTAINERS MORE THAN THREE HIGH. SECURE LOADS AGAINST SHIFTING DURING TRANSPORTATION. USE ONLY AN APPROPRIATE TOOL TO OPEN CONTAINERS.

SAFE STORAGE CONDITIONS: STORE IN COOL, WELL-VENTILATED AREA. MAINTAIN TEMPERATURE BETWEEN 40°F AND 110°F. AVOID EXPOSURE TO DIRECT SUNLIGHT, HEAT OR FLAME. INSPECT CONTAINERS FOR LEAKS PERIODICALLY. ROTATE STOCK, USE OLDER MATERIAL FIRST.

INCOMPATIBILITIES: DO NOT HANDLE OR STORE NEAR WATER-REACTIVE MATERIALS, STRONG OXIDIZERS, ACIDS OR ALKALIS.

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 09/23/2019

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS INGREDIENTS	CAS NUMBER	%WT	ACGIH				OSHA EXPOSURE LIMITS		VAPOR PRESS mmHg @ TEMP
			TLV/TWA	PPM	TWA	MG/M ³	STEL	PPM	

NO REPORTABLE HAZARDOUS INGREDIENTS.

ENGINEERING CONTROLS: USE SIGNS OR BARRIERS TO RESTRICT ACCESS TO PAINTING WORK AREA.

VENTILATION : NORMAL AIR CIRCULATION SHOULD BE SUFFICIENT; OTHERWISE, USE PORTABLE FANS. ENSURE ADEQUATE VENTILATION DURING APPLICATION, DRYING AND CURING OF PAINT.

RESPIRATORY PROTECTION: FOR SPRAY APPLICATION, USE A NIOSH-APPROVED PARTICULATE FILTER MASK (N95 OR HIGHER) TO AVOID BREATHING SPRAY MIST. EXPOSED PERSONS WITH ALLERGIES OR ASTHMA MAY NEED AN ORGANIC VAPOR/PARTICULATE RESPIRATOR (NIOSH/MSHA TC 23C OR EQUIVALENT).

WHEN SANDING, SCRAPING, OR ENGAGING IN ANY ACTIVITY THAT GENERATES AIRBORNE NUISANCE DUST, WEAR A NIOSH-APPROVED PARTICULATE FILTER MASK (N95 OR HIGHER) TO AVOID BREATHING DUST. FINISH BY WATER-WASHING ALL SURFACES TO REMOVE DUST.

EYE PROTECTION: USE SAFETY GLASSES, GOGGLES, OR FACE SHIELD TO PROTECT EYES.

SKIN PROTECTION: USE WATERPROOF GLOVES (LATEX, VINYL, RUBBER, OR NEOPRENE) TO AVOID SKIN CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: WATERPROOF HEADCOVERING AND GENERAL PROTECTIVE CLOTHING ARE RECOMMENDED FOR PROTECTION AS NECESSARY.

WORK HYGIENIC PRACTICES: WASH HANDS AND FACE BEFORE EATING OR DRINKING.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	OPAQUE LIQUID DISPERSION	VAPOR PRESSURE:	SAME AS WATER VAPOR	
ODOR:	VERY MILD ODOR	VAPOR DENSITY:	SAME AS WATER VAPOR	
ODOR THRESHOLD:	(NO INFORMATION AVAILABLE)	SPECIFIC GRAVITY:	~1.4 (H ₂ O = 1)	
pH AS SUPPLIED:	~8.5	SOLUBILITY IN WATER:	PARTLY SOLUBLE	
FREEZING POINT:	0° C / 32° F	PARTITION COEFFICIENT:	(NO INFORMATION AVAILABLE)	
BOILING POINT:	100° C / 212° F	AUTO-IGNITION TEMP:	(NOT APPLICABLE)	
FLASH POINT:	(NOT APPLICABLE)	DECOMPOSITION TEMP:	(NO INFORMATION AVAILABLE)	
EVAPORATION RATE:	SAME AS WATER	VISCOSITY:	85 – 115 KU	
FLAMMABILITY:	(NOT APPLICABLE)	PERCENT SOLIDS:	BY VOL: ~35%	BY WT: ~50%
UPPER EXPLOSIVE LIMIT:	(NOT APPLICABLE)	PERCENT VOLATILE:	BY VOL: ~65%	BY WT: ~50%
LOWER EXPLOSIVE LIMIT:	(NOT APPLICABLE)			

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 09/23/2019

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: REACTIVITY NOT KNOWN TO OCCUR UNDER NORMAL CONDITIONS.

CHEMICAL STABILITY: STABLE UNDER NORMAL CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS: POLYMERIZATION WILL NOT OCCUR.

CONDITIONS TO AVOID: AVOID STORAGE AT TEMPERATURES BELOW 40° F OR ABOVE 110° F.

INCOMPATIBLE MATERIALS: AVOID WATER-REACTIVE MATERIALS, STRONG OXIDIZERS, ACIDS AND ALKALIS.

HAZARDOUS DECOMPOSITION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE: INHALATION, INGESTION, EYE AND SKIN CONTACT

SYMPTOMS OF OVEREXPOSURE: MAY CAUSE MILD IRRITATION TO SKIN AND EYES, GASTROINTESTINAL AND RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND HEADACHE POSSIBLE.

DELAYED OR CHRONIC EFFECTS: AVAILABLE INFORMATION PROVIDES NO EVIDENCE OF DELAYED OR CHRONIC HEALTH EFFECTS ASSOCIATED WITH EXPOSURE TO THIS PRODUCT DURING NORMAL USE WITH RECOMMENDED PERSONAL PROTECTION AS NEEDED.

NUMERICAL MEASURES OF TOXICITY: (NO INFORMATION AVAILABLE)

CARCINOGENICITY: NTP? NO. IARC? NO. OSHA? NO. PROP 65? NO.

HAZARDOUS BY-PRODUCTS: SPRAY APPLICATION OF THIS PRODUCT CAN GENERATE SPRAY MIST, WHICH MAY BE HAZARDOUS TO YOUR HEALTH IF INHALED. RISK DEPENDS ON LEVEL AND DURATION OF EXPOSURE.

SANDING, SCRAPING, OR OTHERWISE DISTURBING THE DRY FILM OF THIS PRODUCT CAN GENERATE AIRBORNE NUISANCE DUST, WHICH MAY BE HAZARDOUS TO YOUR HEALTH IF INHALED. RISK DEPENDS ON LEVEL AND DURATION OF EXPOSURE.

SEE SECTION 8: "EXPOSURE CONTROLS / PERSONAL PROTECTION" FOR INFORMATION ON RESPIRATORY PROTECTION WHEN SPRAYING OR SANDING.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: (NO INFORMATION AVAILABLE)

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: COLLECT SPILLED MATERIAL, USED ABSORBENT MATERIAL AND WIPES INTO A SUITABLE CONTAINER AND DISPOSE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS. DRY, EMPTY CONTAINERS MAY BE RECYCLED OR DISPOSED OF AS ORDINARY TRASH.

RCRA HAZARD CLASS: NON-HAZARDOUS

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 09/23/2019

SECTION 14: TRANSPORT INFORMATION

THIS MATERIAL IS NOT SUBJECT TO DOT, IATA/ICAO, OR IMO/IMDG TRANSPORTATION REGULATIONS.
ACCEPTABLE FOR AIR TRANSPORT AS NON-HAZARDOUS GOODS.

UN NUMBER: (NOT APPLICABLE) UN PROPER SHIPPING NAME: (NOT APPLICABLE)
TRANSPORT HAZARD CLASS: (NOT APPLICABLE) PACKING GROUP: (NOT APPLICABLE)
ENVIRONMENTAL HAZARDS: (NOT APPLICABLE) TRANSPORT IN BULK: (NOT APPLICABLE)
SPECIAL PRECAUTIONS: FOLLOW RECOMMENDED PROCEDURES FOR SAFE HANDLING AND STORAGE.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

TSCA: ALL COMPONENTS ARE LISTED IN TSCA INVENTORY OR EXEMPT.

CERCLA: NOT LISTED AS A HAZARDOUS SUBSTANCE.

SARA TITLE III: NOT LISTED AS A HAZARDOUS SUBSTANCE.

311/312 HAZARD CATEGORIES: (NOT APPLICABLE)

313 REPORTABLE INGREDIENTS: (NOT APPLICABLE)

STATE REGULATIONS: (NOT APPLICABLE)

SECTION 16: OTHER INFORMATION

DATE OF PREPARATION: SEPTEMBER 23, 2019

PREPARER INFORMATION: DUNN-EDWARDS CORPORATION
ENVIRONMENTAL AFFAIRS DEPARTMENT
PHONE: (323) 826-2663

DISCLAIMER: THE INFORMATION CONVEYED ABOVE, ALTHOUGH OBTAINED FROM SOURCES WE CONSIDER RELIABLE, IS FURNISHED BY DUNN-EDWARDS CORPORATION WITHOUT ANY WARRANTY (WHETHER EXPRESS OR IMPLIED) AS TO ITS ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR NEEDS OR CIRCUMSTANCES.